

## Witcobond Dispersions Contact Information

### North America

Witcobond Customer Service  
Phone: 1-877-873-0273

Visit us on the web at  
[www.Chemtura.com](http://www.Chemtura.com)

### Latin America

Chemtura Corporation, S.A. de C.V.  
Calzada de Guadalupe 410  
Col. El Cerrito  
Cuautitlan, Estado de Mexico  
54800, Mexico  
Phone: 52 55 5010 6580 / 5010 6605 / 5010 6502 Sales area  
And 5010 6601 Customer Care

Chemtura Industria Quimica do Brasil Limitada  
Edificio Villa Lobos  
Av. Nacoes Unidas, 4.777, 15o. Andar  
Alto de Pinheiros - Sao Paulo - SP  
CEP 05477-000  
Phone: +011-55-11-3896-1500  
Fax: +011-55-11-3896-1502

### Europe

Baxenden Chemicals Ltd., a Chemtura Company  
Union Lane, Droitwich, Worcestershire  
WR9 9BB, England  
Phone: +011-44-1905-794795  
Fax: +011-44-1905-795083

### Asia

Chemtura Taiwan Ltd.  
RM C, 7F, No. 133, Sec. 3, Minsheng E. Rd.,  
Taipei 105, Taiwan, R.O.C.  
86-15921557826 China cell  
Office: +886-2-27131790  
Fax: +886-2-27125668  
Cell: +886-926168279

The information contained herein is correct to the best of our knowledge. Your attention is directed to the pertinent Material Safety Data Sheets for the products mentioned herein.

All sales are subject to Chemtura's standard terms and conditions of sale, copies of which are available upon request and which are part of Chemtura's invoices and/or order acknowledgments. Except as expressly provided in Chemtura's standard terms and conditions of sale, no warranty, express or implied, including warranty of merchantability or fitness for a particular purpose, is made with respect to the products described herein. Nothing contained herein shall constitute permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.

© Copyright 2011

The tradenames in this brochure are registered trademarks of Chemtura Corporation and/or its subsidiaries.





## Witcobond® Dispersions for Coatings, Adhesives and Textile Binders

### What this chart does:

At a glance you can compare specific properties of our product line. This will aid you in finding the best dispersion for your formulation needs.

### Dispersions for Coatings:

Small particle size for flow and high gloss  
Variable elongation matched to appropriate substrate requirements for adhesion, resistance and weatherability

### Dispersions for Adhesives & Textile Binders:

Anionic, cationic or nonionic  
Variable solids and elongation matched to application requirements for adhesion and resistance

### Epoxy Emulsion Cross-linker for Water-Borne Coatings & Adhesives:

Relatively small, uniform particle size and contains zero VOC  
Improves water and chemical resistance of coating  
Used at 5-7 parts/100 parts of water-borne resin  
Coating must be cured at 120°C for ~20 minutes, for optimum results

Distinctive urethane dispersion technologies provide high-value answers to your performance questions.

Call customer service for performance data sheets and samples: 1-877-873-0273.

